

Please type a plus sign (+) inside this box → ☐ +
Under the paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. CFP-994

First Inventor Bobby HU

Title Ratcheting Tools Having an Angle-Adjustable Head

Express Mail Label No. EM217201982US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington DC 20231

1. ☒ *Fee Transmittal Form (e.g. PTO/SB/17)
(Submit an original and a duplicate for fee processing)

2. ☒ Specification Total Pages (13)

- (preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure

☒ Formal Drawing(s) (35 U.S.C. 113) Total Sheets (23)

☒ Oath or Declaration

a. ☒ Newly executed (original or copy)

b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))

i. ☐ DELETION OF INVENTOR(S)

Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)

6. Nucleotide and/or Amino Acid Sequence Submission
(If applicable, all necessary)

- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))

8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)

9. ☐ English Translation Document (if applicable)

10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations

11. ☐ Preliminary Amendment

12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

13. ☒ *Small Entity ☐ Statement filed in prior application
Statement(s) Status still proper and desired
(PTO/SB/09-12)

14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)

15. ☐ Other:

*NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment.

☐ Continuation

☐ Divisional

☐ Continuation-in-part (CIP)

of prior application no.: _____

Prior application information:

Examiner: _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer No. or Bar Code Label

or ☐ Correspondence address below

(insert Customer No. or Attach bar code label here)

Address **Oppenheimer Wolff & Donnelly LLP**
45 South Seventh Street
3400 Plaza VII

City **Minneapolis**

State

Minnesota

Zip Code

55402

Country

USA

Telephone

612-607-7539

Fax

612-607-7100

Name (Print/Type)

Alan Kamrath

Registration No. (Attorney/Agent)

28,227

Signature

Alan Kamrath

Date

November 5, 1999

Applicant or Patentee: Bobby HU

Docket #: _____

Serial or Patent Number: _____

Examiner: _____

Filed or Issued: _____

Art Unit: _____

For: RATCHETING TOOLS HAVING AN ANGLE-ADJUSTABLE HEAD**VERIFIED STATEMENT (DECLARATION) BY AN INDEPENDENT INVENTOR
CLAIMING SMALL ENTITY STATUS UNDER 37 CFR 1.9(F) AND 1.27(B)**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled RATCHETING TOOLS HAVING AN ANGLE-ADJUSTABLE HEAD

by Bobby HU _____
(Inventor(s))

described in:

- ☒ The specification filed herewith.
☐ Patent application serial number _____, filed _____.
☐ PCT International patent application number _____, filed _____.
☐ Patent number _____, issued _____.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed or licensed or am under an obligation under contract or law to assign, grant, convey or license any rights in the invention is listed below:

- ☒ No such person, concern or organization.
☐ Persons, concerns or organizations listed below. Note: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 CFR 1.27).

Full Name: _____

Address: _____

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

Full Name: _____


Address: _____

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

☐ See attached sheet for additional person(s), concern(s) or organization(s).

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine, or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which the verified statement is directed.

	Inventor 1	Inventor 2	Inventor 3
Name	Bobby HU		
Signature			
Date	November 1, 1999		

RATCHETING TOOLS HAVING AN ANGLE-ADJUSTABLE HEAD

Background of the Invention

1. Field of the Invention

The present invention relates to ratcheting tools of the type having a head that is finely adjustable in an angular position relative to a handle.

2. Description of the Related Art

Figs. 14 and 15 of the drawings illustrate a conventional ratcheting tool having a head 10' adjustable relative to a handle 20'. The head 10' includes an extension 11' with a number of teeth 12' formed on an end thereof. An end of the handle 20' includes two walls having a compartment 21' defined therebetween. A pin 22' is extended through aligned holes (one of them is a screw hole) of the walls of the end of the handle 20' and through a hole (not labeled) in the extension 11' of the head 10'. A longitudinal hole 26' and a transverse hole 27' are defined in the handle 20' and located below the walls, wherein an upper end of the longitudinal hole 26' communicates with the compartment 21' and the transverse hole 27' intersects the longitudinal hole 26' at a mediate portion of the latter. A spring 28' and a ball 29' are mounted in a lower portion of the longitudinal hole 26'. A push pin 30' is extended through the transverse hole 27' and includes a positioning notch 31' in an underside thereof for engaging with the ball 29'. The push pin 30' further includes an inclined face 32' in an upper side thereof. The push pin 30' has a length greater than that of the transverse hole 27' such that two ends of the push pin 30' are exposed outside the handle 20' for manual operation. A ball 33', a spring 34', and a catch 35' are mounted in an upper portion of the longitudinal hole 26', best shown in Fig. 15. The catch 35' includes a receptacle 36' for receiving the spring 34' and a portion of the ball 33' that rests on the inclined face 32'. The catch 35' further includes an inclined underside 37' having the same inclination as the inclined face 32'. The catch 35' is biased upward by the spring 34' to engage with the teeth 12' of the head 10', thereby retaining the head 10' in a desired angular position with respect to the handle 20'. When the push pin 30' is pushed, the lower ball 29' is lowered and the upper ball 33' is also

1 lowered, as shown in Fig. 15. The upper spring 34' and the catch 35' are also lowered such
2 that the catch 35' disengages from the teeth 12' of the head 10'. Thus, the head 10' may be
3 pivoted to a desired angular position relative to the handle 20' and the push pin 30' is then
4 released to thereby retain the head 10' in the desired angular position.

5 Nevertheless, such an arrangement is too complicated (two sets of balls and springs are
6 required) and has limited angular adjustment, since there are only six teeth 12' on the head 10'.
7 The ratcheting tool cannot perform its function if the fastener to be tightened/loosened is
8 located in a position that cannot be reached by the five angular positions of the head. The
9 retaining function of the catch 35' by only one tooth is also too small and thus incapable of
10 reliably retaining the head 10' in place. A further drawback of the complicated structure is that
11 the catch 35' and the teeth 12' tend to disengage from each other when the balls 29' and 33'
12 and the springs 28' and 34' are impinged.

13 Figs. 16 through 18 of the drawings illustrate another conventional ratcheting tool
14 having a head 110' adjustable relative to a handle 120'. The head 110' includes an extension
15 111' with a number of teeth 112' formed on an end thereof. An end of the handle 120'
16 includes two walls having a compartment 121' defined therebetween. A pin 122' is extended
17 through aligned holes (one of them is a screw hole) of the walls of the end of the handle 120'
18 and through a hole (not labeled) in the extension 111' of the head 110'. A longitudinal hole
19 127' and a transverse hole 126' are defined in the handle 120' and located below the walls,
20 wherein an upper end of the longitudinal hole 127' communicates with the compartment 121'
21 and the transverse hole 126' intersects the longitudinal hole 127' at a lower portion of the
22 latter. A turnknob 128' includes a stem 133' extended through the transverse hole 126' and
23 having a stem 133' with a higher profile portion 135' and a lower profile portion 134'. A ball
24 129', a spring 130', and a catch 131' are mounted in an upper portion of the longitudinal hole
25 127', best shown in Fig. 17. The catch 131' includes a receptacle 136' for receiving the spring
26 130' and the ball 129' that rests on the stem 133'. The catch 131' further includes a tooth 137'
27 for engaging with the teeth 112' of the head 110'. When the ball 130' rests on the higher

1 profile portion 135' (Fig. 18), the catch 131' is biased upward by the spring 130' to engage
2 with the teeth 112' of the head 110', thereby retaining the head 110' in a desired angular
3 position with respect to the handle 120'. When the turnknob 128' is turned to a position in
4 which the ball 130' rests on the lower profile portion 134', the ball 130' is lowered. The spring
5 130' and the catch 131' are also lowered such that the tooth 137' of the catch 131' disengages
6 from the teeth 112' of the head 110'. Thus, the head 110' may be pivoted to a desired angular
7 position relative to the handle 120' and the turnknob 128' is then turned to the initial position
8 to thereby retain the head 110' in the desired angular position.

9 Nevertheless, such an arrangement is still too complicated and has limited angular
10 adjustment, since there are only six teeth 112' on the head 110'. The ratcheting tool cannot
11 perform its function if the fastener to be tightened/loosened is located in a position that cannot
12 be reached by the five angular positions of the head. The retaining function of the catch 131'
13 by only one tooth is also too small and thus incapable of reliably retaining the head 110' in
14 place. In addition, the user must use both hands to proceed with such adjustment.

15 **Summary of the Invention**

16 It is a primary object of the present invention to provide a ratcheting tool having a head
17 finely adjustable in an angular position relative to a handle, wherein the ratcheting tool is
18 simpler in structure to allow easy manufacture and assembly and to reduce potential
19 malfunction possibility. Adjustment of the angular position of the head relative to the handle is
20 accomplished by pushing a push button to allow adjustment and then releasing the push button
21 to retain the head in place.

22 A ratcheting tool in accordance with the present invention comprises:

23 a head including an end with an arcuate toothed face;

24 a handle including an end defining a compartment for pivotal connection with the end of
25 the head, the handle including a longitudinal hole having an inner end and an outer end
26 communicated with the compartment, the handle further including a transverse hole
27 communicated with the inner end of the longitudinal hole;

1 a catch mounted in the longitudinal hole and including a first end with an arcuate
2 toothed surface and a second end;

3 a push button mounted in the transverse hole and including a stem, the stem including a
4 relatively higher portion and a relatively lower portion; and

5 means for biasing the push button to a retaining position in which the second end of the
6 catch engages with the relatively higher portion of the stem such that the arcuate toothed
7 surface of the catch is biased to engage with the arcuate toothed face of the head, thereby
8 retaining the head in an angular position relative to the handle, and wherein when the push
9 button is pushed, the second end of the catch is disengaged from the relatively higher portion
10 of the stem such that the arcuate toothed surface of the catch is disengaged from the arcuate
11 toothed face of the head, thereby allowing adjustment of the angular position of the head
12 relative to the handle.

13 A reduced hole may be intercommunicated between the transverse hole and the inner
14 end of the longitudinal hole. The second end of the catch includes a stub extended through the
15 reduced hole, and an elastic member is mounted around the stub for assisting in bias of the
16 catch toward the head when the push button is in its retaining position.

17 The stem of the push button includes an inclined surface for engaging with the second
18 end of the stem. In an embodiment of the invention, the transverse hole includes a countersink
19 in an end thereof to define an end wall. The push button includes a button head from which the
20 stem extends. The biasing means is an elastic member mounted around the stem, located in the
21 countersink, and attached between the end wall and the button head.

22 Other objects, advantages, and novel features of the invention will become more
23 apparent from the following detailed description when taken in conjunction with the
24 accompanying drawings.

25 **Brief Description of the Drawings**

26 Fig. 1 is a perspective view of a ratcheting tool in accordance with the present invention;

1 Fig. 2 is an exploded perspective view of the ratcheting tool in accordance with the
2 present invention;

3 Fig. 3 is a side view, partly sectioned, of the ratcheting tool in accordance with the
4 present invention;

5 Fig. 3A is an enlarged view of a circle A in Fig. 3;

6 Fig. 4 is a view similar to Fig. 3, wherein a push button is pushed;

7 Fig. 4A is an enlarged view of a circle B in Fig. 4;

8 Fig. 5 is a view similar to Fig. 4, wherein a head is pivoted through a small angle;

9 Fig. 5A is an enlarged view of a circle C in Fig. 5;

10 Fig. 6 is a view similar to Fig. 5, wherein the head is pivoted through a larger angle;

11 Fig. 6A is an enlarged view of a circle D in Fig. 6;

12 Fig. 7 is a view similar to Fig. 6A, illustrating a modified embodiment of the push
13 button;

14 Fig. 8 is an exploded perspective view of a modified embodiment of the ratcheting tool
15 in accordance with the present invention;

16 Fig. 9 is a side view, partly sectioned, of the ratcheting tool in Fig. 8;

17 Fig. 9A is an enlarged view of a circle E in Fig. 9;

18 Fig. 10 is a view similar to Fig. 9, wherein a push button is pushed;

19 Fig. 10A is an enlarged view of a circle F in Fig. 10;

20 Fig. 11 is a view similar to Fig. 10, wherein the head is pivoted through an angle and the
21 push button is released;

22 Fig. 11A is an enlarged view of a circle G in Fig. 10;

23 Fig. 12 is a side view, partly sectioned, illustrating application of the ratcheting tool in
24 accordance with the present invention to a tool bit connector;

25 Fig. 13 is a view similar to Fig. 12, wherein a head is adjusted to a desired angular
26 position;

1 Fig. 14 is an exploded perspective view of a conventional ratcheting tool with an
2 adjustable head;

3 Fig. 15 is a side view, partly sectioned, of the ratcheting tool in Fig. 14;

4 Fig. 16 is an exploded perspective view of another conventional ratcheting tool with an
5 adjustable head;

6 Fig. 17 is a side view, partly sectioned, of the ratcheting tool in Fig. 16; and

7 Fig. 18 is a sectional view taken along line 18-18 in Fig. 17.

8 **Detailed Description of the Preferred Embodiments**

9 Referring to Figs. 1 through 13 and initially to Figs. 1 and 2, a ratcheting tool in
10 accordance with the present invention generally includes a handle 10 and a head 50 adjustably
11 connected to the handle 10. The head 50 includes a transverse hole 52 in a first end thereof
12 and a drive column 51 extended from a second end thereof. The first end of the head 50
13 includes an arcuate toothed face with a plurality of teeth 53 formed thereon. The toothed
14 arcuate face may extend for about 180°. It is appreciated that the head 50 may be a head of any
15 kind of ratcheting tools, not limited to the socket wrench type ratcheting tool illustrated.

16 An end 20 of the handle 10 includes two walls 21 and 22 having a compartment 23
17 defined therebetween for receiving the first end of the head 50. A pin 54 is extended through
18 aligned holes 211 and 221 (hole 221 is a screw hole) of the walls 21 and 22 of the end 20 of
19 the handle 10 and through the transverse hole 52 in the head 50. A longitudinal hole 26 and a
20 transverse hole 24 are defined in the handle 10, wherein an outer end of the longitudinal hole
21 26 communicates with the compartment 23 and the transverse hole 27 is communicated with
22 an inner end of the longitudinal hole 26 via a reduced hole 25. A countersink 241 is defined in
23 an end of the transverse hole 27 and defines an end wall 242.

24 A push button 30 includes a button head 31 and a stem 32 extended from the button
25 head 31. The stem 32 is extended through the transverse hole 24 and has a supporting portion
26 33 including a first supporting face 331 and a second supporting face 332 that is lower than
27 the first supporting face 331. The first supporting face 331 is inclined, which will be described

1 later. An elastic member (e.g., a spring 34) is mounted around the stem 32 and located in the
2 countersink 241, as shown in Fig. 3A. The spring 34 is thus attached between the end wall 242
3 and the button head 31 to bias the push button 30 outward.

4 A catch 40 and an elastic member (e.g., a spring 44) are mounted in the longitudinal
5 hole 26 for releasably engaging with the teeth 53 of the head 50. As illustrated in Figs. 2 and
6 3A, the catch 40 includes a body 42 with an arcuate toothed surface 43 formed on a first end
7 thereof and a stub 41 projected from a second end thereof. The spring 44 is mounted around
8 the stub 41 that extends through the reduced hole 25 and rests on the stem 32 of the push
9 button 30.

10 When the push button 30 is in a released position shown in Figs. 3 and 3A, the stub 41
11 of the catch 40 rests on the first supporting face 331 of the stem 32 of the push button 30, and
12 the spring 44 biases the arcuate toothed surface 43 of the catch 40 to engage with the arcuate
13 teeth 53 of the head 50, thereby retaining the head 50 in a desired angular position with respect
14 to the handle 10. The teeth 53 of the head 50 may be engaged with the arcuate toothed surface
15 43 of the catch 40 by more than ten teeth to thereby provide a reliable retaining effect.

16 Referring to Figs. 4 and 4A, when the push button 30 is pushed inward, the stub 41 of
17 the catch 40 disengages from the first supporting face 331 and not engaged with the second
18 supporting face 332 of the push button 30. Thus, the head 50 is pivotable relative to the handle
19 10.

20 Referring to Figs. 5 and 5A, when adjustment of the angular position of the head 50 is
21 required, the head 50 is pivoted and thus causes disengagement of the toothed surface 43 of
22 the catch 40 from the teeth 53 of the head 50. The stub 41 of the catch 40 now rests on the
23 second supporting face 332. Namely, the head 50 is in free rotation during adjustment.

24 Referring to Figs. 6 and 6A, the user may pivot the head 50 to a desired angular position
25 relative to the handle 10 and then releases the push button 30. The head 50 is reliably retained
26 in the desired angular position relative to the handle 10. The relative angular relationship
27 between the head and the handle can be finely adjusted, as the arcuate toothed surface 43 of

1 the catch 90 and the arcuate toothed face of the head 50 may include more teeth. Fig. 7
2 illustrates a modified embodiment of the push button 30, wherein the supporting portion (now
3 designated by 35) of the stem 32 of the push button 30 is modified as an inclined surface 351.

4 Fig. 8 illustrates a modified embodiment of the ratcheting tool in accordance with the
5 present invention. The ratcheting tool includes a handle 60 and a head 100 adjustably
6 connected to the handle 60. The head 100 includes a transverse hole 102 in a first end thereof
7 and a drive column 101 extended from a second end thereof. The first end of the head 100
8 includes an arcuate toothed face with a plurality of teeth 103 formed thereon. The toothed
9 arcuate face may extend for about 180°.

10 An end 70 of the handle 60 includes two walls 71 and 72 having a compartment 73
11 defined therebetween for receiving the first end of the head 100. A pin 104 is extended
12 through aligned holes 711 and 721 (hole 721 is a screw hole) of the walls 71 and 72 of the end
13 70 of the handle 60 and through the transverse hole 102 in the head 100. A longitudinal hole
14 75 and a transverse hole 74 are defined in the handle 60, wherein an outer end of the
15 longitudinal hole 75 communicates with the compartment 73 and the transverse hole 74 is
16 communicated with an inner end of the longitudinal hole 75. A countersink 741 is defined in
17 an end of the transverse hole 74 and defines an end wall 742.

18 A push button 80 includes a button head 81 and a stem 82 extended from the button
19 head 81. The stem 82 is extended through the transverse hole 74 and has a supporting portion
20 83 including a first supporting face 831 and a second supporting face 832 that is lower than
21 the first supporting face 831. The first supporting face 831 is inclined, which will be described
22 later. An elastic member (e.g., a spring 84) is mounted around the stem 82 and located in the
23 countersink 841, as shown in Fig. 9A. The spring 84 is thus attached between the end wall 742
24 and the button head 81 to bias the push button 80 outward.

25 A catch 90 is mounted in the longitudinal hole 75 for releasably engaging with the teeth
26 103 of the head 100. As illustrated in Figs. 8 and 9A, the catch 90 includes a first end 92 with
27 an arcuate toothed surface 93 formed thereon and a second end 91.

1 When the push button 80 is in a released position shown in Fig. 9A, the first end 91 of
2 the catch 90 rests on the first supporting face 831 of the stem 82 of the push button 80. The
3 arcuate toothed surface 93 of the catch 90 is biased toward the head 100 to engage with the
4 arcuate teeth 103 of the head 100, thereby retaining the head 100 in a desired angular position
5 with respect to the handle 60. The teeth 103 of the head 100 may be engaged with the toothed
6 surface 93 of the catch 90 by more than ten teeth to thereby provide a reliable retaining effect.

7 Referring to Figs. 10 and 10A, when the push button 80 is pushed inward, the arcuate
8 toothed surface 93 of the catch 90 disengages from the teeth 103 of the handle 100 with the
9 first end 91 of the catch 90 resting on the second supporting face 832 of the push button 80.
10 Thus, the head 100 is pivotable relative to the handle 100. Referring to Figs. 11 and 11A,
11 when adjustment of the angular position of the head 100 is required, the head 100 is pivoted to
12 a desired angular position relative to the handle 60 and the push button 80 is then released.
13 The head 100 is reliably retained in the desired angular position relative to the handle 60. The
14 relative angular relationship between the head and the handle can be finely adjusted, as the
15 arcuate toothed surface 93 of the catch 90 of the arcuate toothed face of the head 100 may
16 include more teeth.

17 Figs. 12 and 13 illustrate application of the adjustment arrangement to a tool bit
18 connector 200. The tool bit connector 200 may engage with any kind of screwdrivers, sockets,
19 or hex wrenches.

20 According to the above description, it is appreciated that the head of the ratcheting tool
21 in accordance with the present invention may be adjusted to a desired angular position relative
22 to the handle in an easier manner. The overall structure is simple for reducing potential
23 malfunction possibility and is easy to manufacture and assemble. The head is reliably retained
24 in place, and the relative angular relationship between the head and the handle can be finely
25 adjusted.

1 **What is claimed is:**

2 1. A ratcheting tool comprising:

3 a head including an end with an arcuate toothed face;

4 a handle including an end defining a compartment for pivotal connection with the end of
5 the head, the handle including a longitudinal hole having an inner end and an outer end
6 communicated with the compartment, the handle further including a transverse hole
7 communicated with the inner end of the longitudinal hole;

8 a catch mounted in the longitudinal hole and including a first end with an arcuate
9 toothed surface and a second end;

10 a push button mounted in the transverse hole and including a stem, the stem including a
11 relatively higher portion and a relatively lower portion; and

12 means for biasing the push button to a retaining position in which the second end of the
13 catch engages with the relatively higher portion of the stem such that the arcuate toothed
14 surface of the catch is biased to engage with the arcuate toothed face of the head, thereby
15 retaining the head in an angular position relative to the handle, and wherein when the push
16 button is pushed, the second end of the catch is disengaged from the relatively higher portion
17 of the stem such that the arcuate toothed surface of the catch is disengaged from the arcuate
18 toothed face of the head, thereby allowing adjustment of the angular position of the head
19 relative to the handle.

20 2. The ratcheting tool as claimed in claim 1, further comprising a reduced hole
21 intercommunicated between the transverse hole and the inner end of the longitudinal hole, the
22 second end of the catch including a stub extended through the reduced hole, and an elastic
23 member being mounted around the stub for assisting in bias of the catch toward the head when
24 the push button is in its retaining position.

25 3. The ratcheting tool as claimed in claim 1, wherein the stem of the push button includes an
26 inclined surface for engaging with the second end of the stem.

1 4. The ratcheting tool as claimed in claim 1, wherein the transverse hole includes a
2 countersink in an end thereof to define an end wall, the push button including a button head
3 from which the stem extends, the biasing means being an elastic member mounted around the
4 stem, located in the countersink, and attached between the end wall and the button head.

66501.1 665460

Abstract of the Disclosure

A ratcheting tool includes a head including an end with an arcuate toothed face and a handle having an end defining a compartment for pivotal connection with the end of the head. The handle includes a longitudinal hole having an inner end and an outer end communicated with the compartment. The handle further includes a transverse hole communicated with the inner end of the longitudinal hole. A catch is mounted in the longitudinal hole and includes a first end with an arcuate toothed surface and a second end. A push button is mounted in the transverse hole and includes a stem, the stem including a relatively higher portion and a relatively lower portion. An elastic member biases the push button to a retaining position in which the second end of the catch engages with the relatively higher portion of the stem such that the arcuate toothed surface of the catch is biased to engage with the arcuate toothed face of the head, thereby retaining the head in an angular position relative to the handle. When the push button is pushed, the second end of the catch is disengaged from the relatively higher portion of the stem such that the arcuate toothed surface of the catch is disengaged from the arcuate toothed face of the head, thereby allowing adjustment of angular position of the head relative to the handle.





Fig. 1



第二圖




Fig. 3A




Fig. 4




Fig. 4A





Fig. 5

Fig. 5A






Fig. 6A





Fig. 7






Fig. 9




Fig. 9A




Fig. 10




Fig. 10A




Fig. 11




Fig. 11A




Fig. 12





Fig. 13






Fig. 15
PRIOR ART




Fig. 16
PRIOR ART




Fig. 17
PRIOR ART

Fig. 18
PRIOR ART

COMBINED DECLARATION/POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled _____

Ratcheting Tools Having an Angle-Adjustable Head

the specification of which (check one)

☒ is attached hereto☐ was filed on _____
as U. S. Application
Serial No. _____
and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefit(s) under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

<u>88217819</u>	<u>Taiwan</u>	<u>20, October 1999</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	Day/Month/Year Filed	Yes	No
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	Day/Month/Year Filed	Yes	No
_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	Day/Month/Year Filed	Yes	No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37 Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)

POWER OF ATTORNEY:

As a named inventor, I hereby appoint the following attorneys and agent:

Alan D. Kamrath
Reg. No.: 28,227

to prosecute this application and

transact all business in the Patent and Trademark Office connected therewith.

Send correspondence to:

Direct telephone calls to: (612) 607 7539Suite 3400
45 South 7th Street
Minneapolis, Minnesota 55402

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Bobby HUInventor's Signature _____ Date November 1, 1999Residence 8F, No. 536-1, Ta Chin Street, Taichung, Taiwan.Citizenship TaiwanPost Office Address 8F, No. 536-1, Ta Chin Street, Taichung, Taiwan.

Full name of second joint inventor, if any _____

Second Inventor's Signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

(Supply similar information and signature lines for third and subsequent joint inventors.)

555011 6654660